



- Small, snap-in nylon receptacles for low cost, insulated, quick connection or disconnection of your wires, through panels, housings or detachable shrouds.
- Typical uses are data processing and vending machines, motors, power supplies, and controls.
- Non-polarized HEYConnects feature 1/4" (6,4 mm) internal brass male terminals, to mate with standard 1/4" (6,4mm) female Quick-Connects.
- Polarized HEYConnects feature 1/4" (6,4 mm) and 3/16" (4,7 mm) internal brass male terminals, to mate with standard 1/4" and 3/16" female Quick-Connects.
- Two-terminal HEYConnect bodies feature markings that correlate the terminals, front to back.
- Available in double-male and male-solder configurations.
- Consult Heyco for white and other colors.

HEYConnect™ Terminal Bushings

Bushings with Double Male Terminals

TERMINALS		PANEL DIMENSIONS						PART NO.	DESCRIPTION	PART DIM.	
No. of Poles	Width in. mm.	A Mounting Hole Diameter in. mm.		B To Prevent Rotation in. mm.		C Maximum Panel Thickness in. mm.				Black	D Overall Length in. mm.
Non-polarized											
1	.25 6,4	.500	12,7	.47	11,8	.13	3,2	4240	DC 50-1-M/M	.94	23,9
1	.25 6,4	.687	17,4	.64	16,3	.13	3,2	4380	DC 50-1-M/M Tinned		
2	.25 6,4	.687	17,4	.64	16,3	.13	3,2	4440	DC 68-2-M/M	.94	23,9
1	.19 4,8	.687	17,4	.64	16,3	.13	3,2	4428	DC 68-2-M/M Polarized		
Polarized											
1	.19 4,8	.687	17,4	.64	16,3	.13	3,2	4428	DC 68-2-M/M Polarized	.94	23,9

Standard color black.

Bushings with Tinned Male to Solder Terminals

TERMINALS		PANEL DIMENSIONS						PART NO.	DESCRIPTION	PART DIM.	
No. of Poles	Width in. mm.	A Mounting Hole Diameter in. mm.		B To Prevent Rotation in. mm.		C Maximum Panel Thickness in. mm.				Black	D Overall Length in. mm.
Non-polarized											
1	.25 6,4	.500	12,7	.47	11,8	.13	3,2	4270	DC 50-1-M/S-Tinned	.92	23,4
1	.25 6,4	.687	17,4	.64	16,3	.13	3,2	4410	DC 68-1-M/S-Tinned		
2	.25 6,4	.687	17,4	.64	16,3	.13	3,2	4470	DC 68-2-M/S-Tinned	.92	23,4
1	.19 4,8	.687	17,4	.64	16,3	.13	3,2	4468	DC 68-2-M/S-Pol Tinned		
Polarized											
1	.25 6,4	.687	17,4	.64	16,3	.13	3,2	4468	DC 68-2-M/S-Pol Tinned	.92	23,4

Standard color black.

Quick
Specs



HEYConnect™ Terminal Bushings

