

CALRAD


55 Series - SVHS Cables

55-771G High Quality Low Loss SVHS Cable With Gold SVHS 4 pin Connectors

8mm shielded high quality SVHS cable terminated with Calrad 30-608 4-pin SVHS gold plated connectors. Miniature shielded 75 ohm video coax cable, 1-RED, 1-YELLOW. Cable O.D. 8mm/.315". Multi-strand tension baring filler for superb strength. Flexible .042" thick rubber jacket. Individual coax cable diameter .122". Individual foamed PE cable dielectric insulation, O.D. .087". Center conductor 24 awg. Nominal capacitance 16.9pf/ft. Shielding 95% braided copper. Dark gray PVC jacket. Custom lengths also available, please ask your Calrad sales representative for your specific needs.

- 55-771G-3.....3 ft.
- 55-771G-6.....6 ft.
- 55-771G-12.....12 ft.
- 55-771G-25.....25 ft.
- 55-771G-330.....Bulk Cable 330 ft.

Custom Lengths Available



SVHS 4 Pin Mini Din Pinout

55-770G Super-VHS Flat Cables. 4-Pin to 4-Pin Plug – Gold

Flexible S-VHS Cable. Low loss pro style cable for running long lengths. 75 ohm dual flat coax cable. 27 awg wire, spiral copper shielded with black PVC black jacket. molded connectors with gold plated contacts. Capacitance is 55pf/m (16.8pf/ft). Attenuation is approx. .06db/m at 10mHz. Shielded.

- 55-770G-1 1 ft., flat cable
- 55-770G-3 3 ft., flat cable
- 55-770G-6 6 ft., flat cable
- 55-770G-10 10 ft., flat cable
- 55-770G-12 12 ft., flat cable
- 55-770G-15 15 ft., flat cable
- 55-770G-20 20 ft., flat cable
- 55-770G-25 25 ft., flat cable
- 55-770G-30 30 ft., flat cable
- 55-770G-50 50ft., flat cable
- 55-770G-75 75 ft., flat cable
- 55-770G-100 100 ft., flat cable
- 55-770G-1000 1000 ft., spool flat cable . w/ no ends.



Plenum SVHS Cables Available Upon Request. Call Calrad for Details

New Item

55-770GR Round Jacketed SVHS Cable.

Black jacketed, double shielded, non-molded, black anodized male to male molded SVHS video cable. 65% 'OFC' braided copper over 100% foil shield, 7mm O.D.

- 55-770GR-3.....3 ft.
- 55-770GR-6.....6 ft.
- 55-770GR-10.....10 ft.
- 55-770GR-12.....12 ft.
- 55-770GR-15.....15 ft.
- 55-770GR-25.....25 ft.
- 55-770GR-50.....50 ft.
- 55-770GR-100.....100 ft.
- 55-770GR-500.....Bulk Cable 500 ft.



55-773G SVHS 4-Pin Plug to 4-Pin Jack– Gold Connectors

Flexible S-VHS cable. Low loss pro style cable for running long lengths. Gold plated connectors 75 Ohm dual flat coax cable. 27 awg wire, spiral copper shielded with black PVC jacket. Capacitance is 55pf/m (16.8pf/ft). Attenuation is approx. .06db/m at 100mhz. Shielded.

- 55-773G-6 6 ft., flat cable
- 55-773G-10 10 ft., flat cable
- 55-773G-25 25 ft., flat cable



New Item

55-772G High Quality, Low Loss SVHS Cable with Gold SVHS Connectors, Silver Colored

Silver jacketed, triple shielded, High Quality non-molded SVHS video cable male to male. Dual miniature spiral shielded coax cables with 65% 'OFC' braided copper over 100% foil shield coverage, 8mm O.D.

- 55-772G-3.....3 ft.
- 55-772G-6.....6 ft.
- 55-772G-10.....10 ft.
- 55-772G-12.....12 ft.
- 55-772G-15.....15 ft.
- 55-772G-20.....20 ft.
- 55-772G-25.....25 ft.
- 55-772G-50.....50 ft.
- 55-772G-75.....75 ft.
- 55-772G-100.....100 ft.
- 55-772G-250.....Bulk Cable 250 ft.





Metal Connectors with Gold Contacts & Silver Finish

55-774G Right Angle SVHS Cable with Varied Pin Configurations 6 ft.

Right angle gold SVHS cables with 4 pin male gold plated SVHS connectors. Individually shielded 75 ohm coax cables for luminance and chrominance signals. Cable allows for low profile hookups. Reversing the cable provides more connecting options. Overall cable O.D. .23" x .12". 27 awg wire, spiral copper shielded with black PVC jacket. Capacitance is 55pf/m (16.8pf/ft). Attenuation is approx. .06db/m at 100mhz.

- 55-774G-A..... Type 1 to 1
- 55-774G-B..... Type 2 to 2
- 55-774G-C..... Type 1 to 2



TYPE 1

TYPE 2

55-740G Gold Plated SVHS 4-Pin Plug To Blunt Cut End

6 foot flat, shielded flexible S-VHS cable. Low loss pros style cable for running long lengths. 75 ohm dual flat coax cable. 27 awg wire, spiral copper shielded with black PVC jacket. Capacitance is 55pf/m (16.6pf/ft). Attenuation is approx. .06db/m at 10mhz. Gold plated SVHS connector

